

Quantity Schedule

1450 Width Towers

BoSS ZONE:1 to EN 1004: Available in 2 lengths - 1.8m and 2.5m
Internal/External Use - Towers under 2.5m are outside of the scope of EN1004

Component	Weight		Internal/External Platform Height										Internal Use Platform Height													
	1.8	2.5	1.2m	1.7m	2.2m	2.7m	3.2m	3.7m	4.2m	4.7m	5.2m	5.7m	6.2m	6.7m	7.2m	7.7m	8.2m	8.7m	9.2m	9.7m	10.2m	10.7m	11.2m	11.7m	12.2m	
125/150/200mm Castor	3.25	3.25	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Adjustable leg assembly	1.1	1.1	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
1450 2 Rung Ladder Frame	12.63	12.63	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
1450 2 Rung Span Frame	6.71	6.71	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
1450 3 Rung Ladder Frame	15.1	15.1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
1450 3 Rung Span Frame	9.48	9.48	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
1450 4 Rung Ladder Frame	17.57	17.57	1	1	1	1	2	1	2	2	3	2	3	3	4	3	4	4	5	4	5	5	6	5	6	6
1450 4 Rung Span Frame	12.24	12.24	1	1	1	1	2	1	2	2	3	2	3	3	4	3	4	4	5	4	5	5	6	5	6	6
1.8m and 2.5m Fixed Deck	17	23	1	1	1*	2	2	2	2	3	3	3	3	4	4	4	4	3	3	3	3	4	4	4	4	4
1.8m and 2.5m Trap Deck	19	25	1	1	1	1	2	2	2	2	3	3	3	3	4	4	4	3	3	3	3	3	4	4	4	4
1.8m and 2.5m Horizontal Brace	2	2.49	6	6	6	6	10	10	10	10	14	14	14	14	18	18	18	18	22	22	22	22	26	26	26	26
2.1m and 2.7m Diagonal Brace	2.3	2.61	2	3	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	23

NOTE: Above 8.2m it is necessary to reposition platforms during the assembly and dismantling process to reduce the self-weight of the tower and optimise the maximum safe working load.

* If you are unable to position the working platform easily from the ground, you may require an additional fixed platform for this tower height.

IMPORTANT: Please ensure you also read the quantity schedule on page 8.