

# Quantity Schedule

## 850 Width Towers

≡ **BoSS ZONE:1 Ladderspan to EN 1004:** Available in 2 lengths - 1.8m and 2.5m  
Internal/External Use - Towers under 2.5m are outside of the scope of EN1004

Component	Weight		Internal/External										Internal Use													
	1.8	2.5	1.2m	1.7m	2.2m	2.7m	3.2m	3.7m	4.2m	4.7m	5.2m	5.7m	6.2m	6.7m	7.2m	7.7m	8.2m	8.7m	9.2m	9.7m	10.2m	10.7m	11.2m	11.7m	12.2m	
125/150/200mm Castor	3.25	3.25	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Adjustable leg assembly	1.1	1.1	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
850 2 Rung Ladder Frame	9.1	9.1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
850 2 Rung Span Frame	3.52	3.52	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
850 3 Rung Ladder Frame	10.4	10.4	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
850 3 Rung Span Frame	4.99	4.99	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
850 4 Rung Ladder Frame	11.7	11.7	1	1	1	1	2	1	2	2	3	2	3	3	4	3	4	4	4	5	4	5	6	5	6	6
850 4 Rung Span Frame	6.58	6.58	1	1	1	1	2	1	2	2	3	2	3	3	4	3	4	4	4	5	4	5	6	5	6	6
1.8m and 2.5m Fixed Deck	17	23																								
1.8m and 2.5m Trap Deck	19	25	1	1	1*	2	2	2	2	3	3	3	3	4	4	4	4	4	5	5	5	6	6	6	6	6
1.8m and 2.5m Horizontal Brace	2	2.49	6	6	6	6	10	10	10	14	14	14	14	14	18	18	18	18	22	22	22	22	26	26	26	26
2.1m and 2.7m Diagonal Brace	2.3	2.61	2	3	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	23

If you are unable to position the working platform easily from the ground, you may require an additional fixed platform for this tower height.