



GLOPOSTS

Glopost and Springback posts plus Unibase™ and bolts

TRAFFIC MANAGEMENT

GLOPOST



UNIBASE™:

Unibase™ can be fitted via the glue matt or by the asphalt or concrete bolts



SPRINGBACK CYLINDER



Conformity

The Springback Cylinder and Glopost both conform to BS 873: Part 8:1985 Category A, Designation 2 (when appropriate sleeve is fitted)
The cone sleeve conforms to: BS 873 : Part 6 : 1983 Category A, Designation 2.

Glopost

Blow moulded from UV Stabilised Low Density Polyethylene

Sealbrite™ class R1B Sleeve

Twist lock designed base to suit either permanent metal cats eye sockets or temporary base

Suitable for use with Unibase™ (sold separately)

Springback post

Rotationally moulded post made from UV Stabilised Low Density Polyethylene

Has an integral shock cord device which allows post to revert to upright position after impact

Springback Cylinder comes complete with Sealbrite™ class R1B Sleeve

Comes complete with screwfit 2 part base connector to fit Unibase™

CLEANING & MAINTENANCE

The Sealbrite™ sleeve and Glopost/Springback Cylinder should be cleaned with a mild road film detergent solution and a cloth

Abrasive substances or solvents will damage the cone sleeve and reduce its performance

LIMITATIONS OF USE

The Glopost and Springback Cylinder must be assembled as per the instructions supplied with product in order to work properly

The post/cylinder & sleeve must be kept clean in order to meet the regulations stated

Belfast:-
103 Airport Road West
Belfast
BT3 9ED
Tel: +44 (0) 28 9045 4599

Ashbourne-
Units 1&2 Greene Park
Ratoath Road
Ashbourne
Co. Meath
A84 XD98
Tel: +353 (01) 802 7173

Email:- info@ridgeway-online.com
Web:- www.ridgeway-online.com



GLOPOSTS

Glopost and Springback posts plus Unibase™ and bolts

G
L
O
P
O
S
T



UNIBASE™



S
P
R
I
N
G
B
A
C
K
C
Y
L
I
N
D
E
R



DIMENSIONS

	Glopost	Springback	Unibase
Height:	750mm/1000mm	750mm/450mm	150mm
Width:	40mm	40mm	270mm
Length:	40mm	40mm	270mm
Weight:	2kg	2kg	1.5Kg

INSTRUCTIONS FOR USE

Distribution of the Glopost and Springback Cylinders must be as per the requirements of: The Traffic Signs Regulations and General Directions 2002 Safety at Street Works and Road Works

Attach the cylinder to the unibase™ as per the instructions supplied

Unibase™ can be fixed to the ground using a Glue Mat or fixings suitable for either Asphalt or Concrete, all of which are available from Ridgeway.



Belfast:-
103 Airport Road West
Belfast
BT3 9ED
Tel: +44 (0) 28 9045 4599

Ashbourne-
Units 1&2 Greene Park
Ratoath Road
Ashbourne
Co. Meath
A84 XD98
Tel: +353 (01) 802 7173

Email:- info@ridgeway-online.com
Web:- www.ridgeway-online.com